

# >>> BELASTINGTABEL HEA BALKEN



Maximum toelaatbare gelijkmatig verdeelde belasting in kg bij een overspanning in meters van: HEA  
De cijfers gelden voor een balk, vrij opgelegd aan de uiteinden, rekening houdend met het eigen gewicht.

HEA	2	2,5	3	3,5	4	5	6	7	8	9	10	11	12
100	3.470	2.761	2.285	1.943									
120	5.048	4.020	3.332	2.837									
140	7.390	5.890	4.885	4.164	3.621	2.852							
160	10.499	8.372	6.948	6.127	5.158	4.072							
180	14.041	11.200	9.301	7.939	6.914	5.467	4.491						
200	18.587	14.831	12.321	10.521	9.166	7.257	5.970	5.038					
220	24.619	19.649	16.328	13.948	12.158	9.635	7.937	6.709					
240	32.279	25.769	21.419	18.303	15.958	12.658	10.438	8.835	7.617				
260		31.931	26.547	22.691	19.791	15.710	12.699	11.174	9.486				
280		38.593	32.190	27.435	23.934	19.010	15.701	13.316	11.508	10.085			
300			40.055	34.250	29.886	23.750	19.630	16.661	14.413	12.645			
320			47.067	40.252	35.129	27.928	23.094	19.613	16.979	14.907	13.232		
340			53.445	45.665	39.900	31.731	26.250	22.281	19.320	16.963	15.078	13.461	11.280
360			60.144	51.394	44.912	35.728	39.568	25.109	21.784	19.139	17.024	15.211	13.776
400					54.940	43.727	26.210	30.772	36.720	23.499	20.926	18.722	16.980