

>>> BELASTINGTABEL IPE BALKEN



Maximum toelaatbare gelijkmatig verdeelde belasting in kg bij een overspanning in meters van: IPE
De cijfers gelden voor een balk, vrij opgelegd aan de uiteinden, rekening houdend met het eigen gewicht.

IPE	2	3	4	5	6	7	8	9	10	11	12
80	948	622	456								
100	1.625	1.070	788	617							
120	2.523	1.665	1.230	966	786						
140	3.684	2.434	1.803	1.419	1.159	969					
160	5.200	3.441	2.553	2.014	1.649	1.385	1.182				
180	6.970	4.616	3.429	2.709	2.223	1.870	1.602	1.388			
200	9.267	6.141	4.566	3.613	2.970	2.503	2.149	1.867	1.638		
220	12.000	7.990	5.940	4.710	3.880	3.270	2.810	2.450	2.160	1.910	1.700
240	15.490	10.276	7.653	6.037	5.000	4.228	3.642	3.180	2.803	2.490	2.224
270	20.520	13.620	10.150	8.056	6.648	5.630	4.860	4.250	3.757	3.347	3.000
300	26.652	17.697	13.200	10.484	8.660	7.344	6.346	5.562	4.925	4.397	3.950
330	34.126	22.670	16.915	13.444	11.114	9.435	8.163	7.163	6.354	5.682	5.115
360	43.278	28.757	21.468	17.071	14.121	11.997	10.391	9.129	8.107	7.261	6.547
400	5.547	36.921	27.575	21.940	18.162	15.444	13.390	11.777	10.473	9.394	8.484